

## Vertical Air receivers from 50L to 1000L

Vessel Size in litres													
	50	80	120	150	200	230	300	350	500	570	800	860	1000
<b>A</b>	1030	1090	1090	1675	1530	1675	1660	1960	2035	2345	2100	2415	2585
<b>B</b>	315	315	315	315	315	315	289	289	338	338	389	389	389
<b>C</b>	610	610	610	1220	1066	1220	1220	1495	1495	1830	1495	1830	2000
<b>D</b>	150	150	150	150	150	203	203	230	230	230	230	230	305
<b>E</b>	305	381	463	381	463	463	508	508	608	608	738	738	738
<b>F</b>	1/4"	1/4"	1/4"	1/4"	3/8"	3/8"	3/8"	3/8"	1/2"	1/2"	1/2"	1/2"	1/2"
<b>G</b>	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"
<b>H</b>	3/4"	3/4"	3/4"	3/4"	1"	1"	1-1/4"	1-1/4"	2"	2"	2"	2"	2"
<b>J</b>	1-1/4"	2"	2"	2"	2"	2"	2"	2"	2"	4 x 3"	2"	4 x 3"	4 x 3"
<b>K</b>	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"
<b>L</b>	150	150	200	150	200	200	200	200	200	200	200	200	200
<b>M</b>				50	64	64	89	89	100	100	150	150	150
<b>N</b>	75	75	75	75	75	75	75	75	75	150	150	150	150
<b>Weight (kg)</b>	35	42	50	70	85	93	115	130	180	200	242	275	300

- |          |                                     |          |   |
|----------|-------------------------------------|----------|---|
| <b>A</b> | Overall Height                      | <b>G</b> | Pressure gauge port                               |
| <b>B</b> | Height from base to bottom of shell | <b>H</b> | Inlet and outlet port                             |
| <b>C</b> | Shell length                        | <b>J</b> | Inspection ports complete with plugs or covers    |
| <b>D</b> | Distance from end of shell to ports | <b>K</b> | Drain port  |
| <b>E</b> | Outside diameter of shell           | <b>L</b> | Distance from centre line                         |
| <b>F</b> | Relief valve port                   | <b>M</b> | Distance to lifting lug from centre of dished end |
|          |                                     | <b>N</b> | Distance from outlet to top of nameplate          |

All Dims in mm unless otherwise stated.  
All screwed connects BSP.



